


BUTT-WELD-FITTING - ASME B16.9/MSS SP-75


LONG RADIUS ELBOWS



90° long radius Elbow



90° long radius Elbow



45° long radius Elbow

ASME B16.9			
N.B	O.D. AT BEVEL	A (mm)	B (mm)
1/2"	21.3	38	16
3/4"	26.7	38	19
1"	33.4	38	22
1 1/4"	42.2	48	25
1 1/2"	48.3	57	29
2"	60.3	76	35
2 1/2"	73.0	95	44
3"	88.9	114	51
3 1/2"	101.6	133	57
4"	114.3	152	64
5"	141.3	190	79
6"	168.3	229	95
8"	219.1	305	127
10"	273.0	381	159
12"	32.8	457	190
14"	355.6	533	222
16"	406.4	610	254
18"	457.0	686	286
20"	508.0	762	318
22"	559.0	838	343
24"	610.0	914	381
26"	660.0	991	406
28"	711.0	1067	438
30"	762.0	1143	470
32"	813.0	1219	502
34"	864.0	1295	533
36"	914.0	1372	565
38"	965.0	1448	600
40"	1016.0	1524	632
42"	1067.0	1600	660
44"	1118.0	1676	695
46"	1168.0	1753	727
48"	1219.0	1829	759

MSS-SP-75			
N.B.	O.D. AT BEVEL	A (mm)	B (mm)
16"	406.4	610	254
18"	457.0	686	286
20"	508.0	762	318
22"	559.0	838	343
24"	610.0	914	381
26"	660.0	991	406
28"	711.0	1067	438
30"	762.0	1143	470
32"	813.0	1219	502
34"	864.0	1295	533
36"	914.0	1372	565
38"	965.0	1448	600
40"	1016.0	1524	632
42"	1067.0	1600	660
44"	1118.0	1676	695
46"	1168.0	1753	727
48"	1219.0	1829	759